

## Description

Rheomix 750 S admixture is a new generation plasticizer based on Glenium® polycarboxylate dispersant technology. This unique chemistry maximizes production efficiency through its cement dispersing and reactive lubricant mechanisms.

## Applications

Recommended for use in:

- Concrete block
- Dry-cast pipe
- Paving stones
- Hollow-core plank
- Concrete roofing tile
- Segmental retaining wall units

# RHEOMIX® 750 S

## Plasticizing Admixture

### Features

- Moderate to heavy swipe texture
- Advanced cement and pigment dispersion
- Provides optimal material flow and extrusion characteristics

### Benefits

- Increases production rate
- Added visual appeal
- Increases compressive and flexural strengths
- Improves compactability
- Reduces breakage and culls
- Potential cement reduction
- Extends life of molds and machine parts
- Increases overall profitability

### Guidelines for Use

**Dosage:** The recommended dosage range for Rheomix 750 S admixture is 2-5 fl oz/cwt (130-325 mL/100 kg) of cement. Please consult with your BASF Construction Chemicals representative if dosages outside of the stated ranges are being considered.

**Mixing:** For maximum efficiency, add Rheomix 750 S admixture after wetting of aggregates and cement, and after at least 75% of the final mix water has been added. Allow at least 90 seconds of additional mix time after Rheomix 750 S admixture has been dispensed.

### Storage and Handling

**Storage Temperature:** If Rheomix 750 S admixture freezes, thaw at 35 °F (2 °C) or above and completely reconstitute by mild mechanical agitation. **Do not use pressurized air for agitation.**

**Shelf Life:** Rheomix 750 S admixture has a minimum shelf life of 12 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your BASF Construction Chemicals representative regarding suitability for use and dosage recommendations if the shelf life of Rheomix 750 S admixture has been exceeded.

# Product Data: RHEOMIX® 750 S

## Packaging

Rheomix 750 S admixture is available in 55 gal (208 L) drums, 275 gal (1040 L) totes and by bulk delivery.

## Related Documents

Material Safety Data Sheets: Rheomix 750 S admixture.

## Additional Information

For additional information on Rheomix 750 S admixture, consult your local BASF Construction Chemicals representative.

*The Admixture Systems business of BASF Construction Chemicals is a leading provider of innovative additives for specialty concrete used in the ready mix, precast, manufactured concrete products, underground construction and paving markets throughout the NAFTA region. The Company's respected Master Builders brand products are used to improve the placing, pumping, finishing, appearance and performance characteristics of concrete.*

**BASF Construction Chemicals, LLC**  
Admixture Systems

[www.masterbuilders.com](http://www.masterbuilders.com)

United States 23700 Chagrin Boulevard, Cleveland, Ohio 44122-5544 ■ Tel: 800 628-9990 ■ Fax: 216 839-8821  
Canada 1800 Clark Boulevard, Brampton, Ontario L6T 4M7 ■ Tel: 800 387-5862 ■ Fax: 905 792-0651

© Construction Research & Technology GMBH

© BASF Construction Chemicals, LLC 2007 ■ Printed in USA ■ 03/07 ■ LIT # 1020180

**Master  
Builders**